

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : **09-093646**

(43)Date of publication of application : **04.04.1997**

(51)Int.Cl.

**H04Q 7/38**

**H04L 5/00**

(21)Application number : **07-242091**

(71)Applicant : **N T T IDO TSUSHINMO KK**

(22)Date of filing : **20.09.1995**


(72)Inventor : **KAMIBAYASHI SHINJI  
TANNO MOTOHIRO**

## (54) MOBILE BODY COMMUNICATION SYSTEM, BASE STATION AND MOBILE STATION

(57)Abstract:

**PROBLEM TO BE SOLVED:** To keep high throughput by controlling the system such that a transmission probability is increased when traffic is small and the transmission probability is decreased when traffic is high thereby reducing collision probability.

**SOLUTION:** Upon the receipt of a signal of an access channel sent by mobile stations 10, 20, a base station 30 uses a transmitter-receiver 31 to demodulate the signal and a reception base band signal is outputted to a traffic measurement section 32 and a base band signal processing section 34. The traffic measurement section 32 measures a valid reception packet number R in the unit time and outputs the measurement result R to a transmission probability calculation section 33 as traffic information and the transmission probability calculation section 33 calculates a transmission probability P. When a transmission



packet is provided, the transmission packet is sent by the same probability as the transmission probability to reduce collision probability to keep a high throughput.